

§ 25.133

47 CFR Ch. I (10–1–14 Edition)

(d) For each new or modified transmitting antenna over 3 meters in diameter, except antennas subject to measurement under §25.138(d), the following on-site verification measurements must be completed at one frequency on an available transponder in each frequency band of interest and submitted to the Commission.

(1) Co-polarized patterns in the elevation plane, plus and minus 7 degrees, in the transmit band.

(2) Co-polarized patterns in the azimuth and elevation planes, plus and minus 7 degrees, in the receive band.

(3) *System cross-polarization discrimination on-axis*. The FCC envelope specified in §25.209 shall be superimposed on each pattern. The transmit patterns are to be measured with the aid of a cooperating earth station in coordination with the satellite system control center under the provisions of §25.272.

(e) Certification that the tests required by paragraph (c) of this section have been satisfactorily performed shall be provided to the Commission in notification that construction of the facilities has been completed as required by §25.133.

(f) Antennas less than 3 meters in diameter and antennas on simple (manual) drive mounts that are operated at a fixed site are exempt from the requirements of paragraphs (c) and (d) of this section provided that a detailed technical showing is made that confirms proper installation, pointing procedures, and polarization alignment and manufacturing quality control. These showing must also include a plan for periodic testing and field installation procedures and precautions.

(g) Records of the results of the tests required by this section must be maintained at the antenna site or the earth station operator's control center and be available for inspection.

[58 FR 13419, Mar. 11, 1993, as amended at 69 FR 5710, Feb. 6, 2004; 70 FR 32253, June 2, 2005; 72 FR 50028, Aug. 29, 2007; 74 FR 47102, Sept. 15, 2009; 74 FR 57098, Nov. 4, 2009; 78 FR 14926, Mar. 8, 2013; 79 FR 8318, Feb. 12, 2014]

**§ 25.133 Period of construction; certification of commencement of operation.**

(a)(1) Each initial license for an earth station governed by this part, except

for blanket licenses, will specify as a condition therein the period in which construction of facilities must be completed and station operation commenced. Construction of the earth station must be completed and the station must be brought into operation within 12 months from the date of the license grant except as may be determined by the Commission for any particular application.

(2) Each initial blanket license for multiple earth stations at unspecified locations will specify as a condition therein the period in which station operation must be commenced. The networks in which the mobile earth stations will be operated must be brought into operation within 12 months from the date of the license grant except as may be determined by the Commission for any particular application.

(b)(1) Each initial license for a transmitting earth station or modified license authorizing operation of an additional transmitting antenna, except for blanket licenses, will also specify as a condition therein that upon completion of construction, the licensee must file with the Commission a certification containing the following information:

- (i) The name of the licensee;
- (ii) File number of the application;
- (iii) Call sign of the antenna;
- (iv) Date of the license;

(v) A certification that the facility as authorized has been completed and that each antenna has been tested and found to perform within 2 dB of the applicable pattern specified in §25.209 or other authorized pattern;

(vi) The date on which the earth station became operational; and

(vii) A statement that the station will remain operational during the license period unless the license is submitted for cancellation.

(2) For earth stations authorized under any blanket licensing provision in this chapter, a certification containing the information in paragraph (b)(1) of this section must be filed when the network is put into operation.

(c) If the facility does not meet the technical parameters set forth in §25.209, a request for a waiver must be submitted and approved by the Commission before operations may commence.

(d) Each receiving earth station licensed or registered pursuant to § 25.131 must be constructed and placed into service within 6 months after coordination has been completed. Each licensee or registrant must file with the Commission a certification that the facility is completed and operating as provided in paragraph (b) of this section, with the exception of certification of antenna patterns.

[56 FR 24016, May 28, 1991, as amended at 58 FR 68059, Dec. 23, 1993; 59 FR 53327, Oct. 21, 1994; 65 FR 59142, Oct. 4, 2000; 70 FR 32254, June 2, 2005; 78 FR 8421, Feb. 6, 2013; 79 FR 8318, Feb. 12, 2014]

**§ 25.134 Licensing provisions for Very Small Aperture Terminal (VSAT) and C-band Small Aperture Terminal (CSAT) networks.**

(a)(1) [Reserved]

(2) *Large Networks of Small Antennas operating in the 4/6 GHz frequency bands.* All applications for digital and/or analog operations will be routinely processed provided the network employs antennas that are 4.5 meter or larger in diameter, that are consistent with § 25.209, the power levels are consistent with §§ 25.211(d) and 25.212(d), and frequency coordination has been satisfactorily completed. The use of smaller antennas or non-consistent power levels require the filing of an initial lead application (§ 25.115(c)(2)) that includes all technical analyses required to demonstrate that unacceptable interference will not be caused to any and all affected adjacent satellite operators by the operation of the non-conforming earth station.

(b) *VSAT networks operating in the 12/14 GHz band.* An applicant for a VSAT network authorization proposing to operate with transmitted power spectral density and/or antenna input power in excess of the values specified in paragraph (g) of this section must comply with the requirements in § 25.220.

(c) [Reserved]

(d) An application for VSAT authorization shall be filed on FCC Form 312, Main Form and Schedule B.

(e) VSAT networks operating in the 12/14 GHz bands may use more than one hub earth station, and the hubs may be sited at different locations.

(f) 12/14 GHz VSAT operators may use temporary fixed earth stations as hub earth stations or remote earth stations in their networks, but must specify, in their license applications, the number of temporary fixed earth stations they plan to use.

(g) Applications for VSAT operation in the 12/14 GHz bands that meet the following requirements will be routinely processed:

(1) Equivalent antenna diameter is 1.2 meters or more and the application includes certification of conformance with relevant antenna performance standards in § 25.209 pursuant to § 25.132(a)(1).

(2) The maximum transmitter power spectral density of a digital modulated carrier into any GSO FSS earth station antenna does not exceed  $-14.0 - 10\log(N)$  dB(W/4 kHz). For a VSAT network using a frequency division multiple access (FDMA) or a time division multiple access (TDMA) technique, N is equal to one. For a VSAT network using a code division multiple access (CDMA) technique, N is the maximum number of co-frequency simultaneously transmitting earth stations in the same satellite receiving beam.

(3) The maximum GSO FSS satellite EIRP spectral density of the digital modulated emission does not exceed 10 dB(W/4kHz) for all methods of modulation and accessing techniques.

(4) Any earth station applicant filing an application to operate a VSAT network in the 12/14 GHz bands and planning to use a contention protocol must certify that its contention protocol usage will be reasonable.

(5) The maximum transmitter power spectral density of an analog carrier into any GSO FSS earth station antenna does not exceed  $-8.0$  dB(W/4kHz) and the maximum GSO FSS satellite EIRP spectral density does not exceed  $+17.0$  dB(W/4kHz).

(h) VSAT operators licensed pursuant to this section are prohibited from using remote earth stations in their networks that are not designed to stop