

tracking, and command communication with the space station(s) in question.

(b) The information required by paragraph (a) of this section must be filed electronically in the Commission's International Bureau Filing System (IBFS), in the "Other Filings" tab of the space station's current authorization file. If call sign or location information provided pursuant to paragraph (a) of this section becomes invalid due to a change of circumstances, the space station operator must file updated information in the same manner within 30 days, except with respect to changes less than 30 days in duration, for which no update is necessary.

[79 FR 8321, Feb. 12, 2014]

§ 25.173 Results of in-orbit testing.

(a) Space station operators must measure the co-polarized and cross-polarized performance of space station antennas through in-orbit testing and submit the measurement data to the Commission upon request.

(b) Within 15 days after completing in-orbit testing of a space station licensed under this part, the operator must notify the Commission that such testing has been completed and certify that the space station's measured performance is consistent with the station authorization and that the space station is capable of using its assigned frequencies or inform the Commission of any discrepancy. The licensee must also indicate in the filing whether the space station has been placed in the assigned geostationary orbital location or non-geostationary orbit. If the licensee files a certification pursuant to this paragraph before the space station has been placed in its assigned orbit or orbital location, the licensee must separately notify the Commission that the space station has been placed in such orbit or orbital location within 3 days after such placement and that the station's measured performance is consistent with the station authorization.

[79 FR 8321, Feb. 12, 2014]

Subpart C—Technical Standards

SOURCE: 30 FR 7176, May 28, 1965; 36 FR 2562, Feb. 6, 1971, unless otherwise noted.

§ 25.201 [Reserved]

§ 25.202 Frequencies, frequency tolerance, and emission limits.

(a)(1) *Frequency band.* The following frequencies are available for use by the Fixed-Satellite Service. Precise frequencies and bandwidths of emission shall be assigned on a case-by-case basis. Refer to the U.S. Table of Frequency Allocations, 47 CFR 2.106, including relevant footnotes, for band-specific use restrictions and coordination requirements. Restrictions and coordination conditions not mentioned in the Table of Frequency Allocations are set forth in the annotations to the following list:

Space-to-earth (GHz)	Earth-to-space (GHz)
3.6–3.65	5.091–5.25
3.65–3.7	5.85–5.925
3.7–4.2	5.925–6.425
4.5–4.8	6.425–6.525
6.7–7.025	6.525–6.7
7.025–7.075	6.7–7.025
10.7–11.7	7.025–7.075
11.7–12.2	12.7–12.75
12.2–12.7	12.75–13.25
18.3–18.58 ^{1,2}	13.75–14
18.58–18.8	14–14.2
18.8–19.3	14.2–14.5
19.3–19.7	15.43–15.63
19.7–20.2	17.3–17.8
37.5–40 ³	24.75–25.05
40–42	25.05–25.25
	² 27.5–28.35
	⁴ 28.35–28.6
	⁵ 28.6–29.1
	⁶ 29.1–29.25
	⁷ 29.25–29.5
	⁴ 29.5–30.0
	47.2–50.2

¹ The 18.3–18.58 GHz band is shared co-equally with existing terrestrial radiocommunication systems until November 19, 2012.

² FSS is secondary to LMDS in this band.

³ Use of this band by the Fixed-Satellite Service is limited to gateway earth station operations, provided the licensee under this part obtains a license under part 101 of this chapter or an agreement from a part 101 licensee for the area in which an earth station is to be located. Satellite earth station facilities in this band may not be ubiquitously deployed and may not be used to serve individual consumers.

⁴ This band is primary for GSO FSS and secondary for NGSO FSS.

⁵ This band is primary for NGSO FSS and secondary for GSO FSS.

⁶ This band is primary for MSS feeder links and LMDS hub-to-subscriber transmission.

⁷ This band is primary for MSS feeder links and GSO FSS.

(2) [Reserved]

(3) The following frequencies are available for use by the non-voice, non-geostationary mobile-satellite service:

137–138 MHz: Space-to-Earth
 148–150.05 MHz: Earth-to-space
 399.9–400.05 MHz: Earth-to-space
 400.15–401 MHz: Space-to-Earth