

Federal Communications Commission

§76.617

§76.613 Interference from a multi-channel video programming distributor (MVPD).

(a) Harmful interference is any emission, radiation or induction which endangers the functioning of a radio-navigation service or of other safety services or seriously degrades, obstructs or repeatedly interrupts a radiocommunication service operating in accordance with this chapter.

(b) An MVPD that causes harmful interference shall promptly take appropriate measures to eliminate the harmful interference.

(c) If harmful interference to radio communications involving the safety of life and protection of property cannot be promptly eliminated by the application of suitable techniques, operation of the offending MVPD or appropriate elements thereof shall immediately be suspended upon notification by the District Director and/or Resident Agent of the Commission's local field office, and shall not be resumed until the interference has been eliminated to the satisfaction of the District Director and/or Resident Agent. When authorized by the District Director and/or Resident Agent, short test operations may be made during the period of suspended operation to check the efficacy of remedial measures.

(d) The MVPD may be required by the District Director and/or Resident Agent to prepare and submit a report regarding the cause(s) of the interference, corrective measures planned or taken, and the efficacy of the remedial measures.

[42 FR 41296, Aug. 16, 1977, as amended at 62 FR 61031, Nov. 14, 1997]

§76.614 Cable television system regular monitoring.

Cable television operators transmitting carriers in the frequency bands 108–137 and 225–400 MHz shall provide for a program of regular monitoring for signal leakage by substantially covering the plant every three months. The incorporation of this monitoring program into the daily activities of existing service personnel in the discharge of their normal duties will generally cover all portions of the system and will therefore meet this requirement. Monitoring equipment and pro-

cedures utilized by a cable operator shall be adequate to detect a leakage source which produces a field strength in these bands of 20 uV/m or greater at a distance of 3 meters. During regular monitoring, any leakage source which produces a field strength of 20 uV/m or greater at a distance of 3 meters in the aeronautical radio frequency bands shall be noted and such leakage sources shall be repaired within a reasonable period of time.

NOTE 1 TO §76.614: Section 76.1706 contains signal leakage recordkeeping requirements applicable to cable operators.

[65 FR 53616, Sept. 5, 2000]

§76.616 Operation near certain aeronautical and marine emergency radio frequencies.

(a) The transmission of carriers or other signal components capable of delivering peak power levels equal to or greater than 10^{-5} watts at any point in a cable television system is prohibited within 100 kHz of the frequency 121.5 MHz, and is prohibited within 50 kHz of the two frequencies 156.8 MHz and 243.0 MHz.

(b) At any point on a cable system from 405.925 MHz to 406.176 MHz analog transmissions are prohibited from delivering peak power levels equal to or greater than 10^{-5} watts. The transmission of digital signals in this range is limited to power levels measured using a root-mean-square detector of less than 10^{-5} watts in any 30 kHz bandwidth over any 2.5 millisecond interval.

[69 FR 57862, Sept. 28, 2004]

§76.617 Responsibility for interference.

Interference resulting from the use of cable system terminal equipment (including subscriber terminal, input selector switch and any other accessories) shall be the responsibility of the cable system terminal equipment operator in accordance with the provisions of part 15 of this chapter: provided, however, that the operator of a cable system to which the cable system terminal equipment is connected shall be responsible for detecting and eliminating any signal leakage where that

leakage would cause interference outside the subscriber's premises and/or would cause the cable system to exceed the Part 76 signal leakage requirements. In cases where excessive signal leakage occurs, the cable operator shall be required only to discontinue service to the subscriber until the problem is corrected.

[53 FR 46619, Nov. 18, 1989]

§§ 76.618–76.620 [Reserved]

§ 76.630 Compatibility with consumer electronics equipment.

(a) Cable system operators shall not scramble or otherwise encrypt signals delivered to a subscriber on the basic service tier.

(1) This prohibition shall not apply in systems in which:

(i) No encrypted signals are carried using the NTSC system; and

(ii) The cable system operator offers to its existing subscribers who subscribe only to the basic service tier without use of a set-top box or CableCARD at the time of encryption the equipment necessary to descramble or decrypt the basic service tier signals (the subscriber's choice of a set-top box or CableCARD) on up to two television sets without charge or service fee for two years from the date encryption of the basic service tier commences; and

(iii) The cable system operator offers to its existing subscribers who subscribe to a level of service above "basic only" but use a digital television or other device with a clear-QAM tuner to receive only the basic service tier without use of a set-top box or CableCARD at the time of encryption, the equipment necessary to descramble or decrypt the basic service tier signals (the subscriber's choice of a set-top box or CableCARD) on one television set without charge or service fee for one year from the date encryption of the basic service tier commences; and

(iv) The cable system operator offers to its existing subscribers who receive Medicaid and also subscribe only to the basic service tier without use of a set-top box or CableCARD at the time of encryption the equipment necessary to descramble or decrypt the basic service tier signals (the subscriber's choice of a set-top box or CableCARD) on up to

two television sets without charge or service fee for five years from the date encryption of the basic service tier commences;

(v) The cable system operator notifies its existing subscribers of the availability of the offers described in paragraphs (ii) through (iv) of this section at least 30 days prior to the date encryption of the basic service tier commences and makes the offers available for at least 30 days prior to and 120 days after the date encryption of the basic service tier commences. The notification to subscribers must state:

On (DATE), (NAME OF CABLE OPERATOR) will start encrypting (INSERT NAME OF CABLE BASIC SERVICE TIER OFFERING) on your cable system. If you have a set-top box, digital transport adapter (DTA), or a retail CableCARD device connected to each of your TVs, you will be unaffected by this change. However, if you are currently receiving (INSERT NAME OF CABLE BASIC SERVICE TIER OFFERING) on any TV without equipment supplied by (NAME OF CABLE OPERATOR), you will lose the ability to view any channels on that TV.

If you are affected, you should contact (NAME OF CABLE OPERATOR) to arrange for the equipment you need to continue receiving your services. In such case, you are entitled to receive equipment at no additional charge or service fee for a limited period of time. The number and type of devices you are entitled to receive and for how long will vary depending on your situation. If you are a (INSERT NAME OF CABLE BASIC SERVICE TIER OFFERING) customer and receive the service on your TV without (NAME OF CABLE OPERATOR)-supplied equipment, you are entitled to up to two devices for two years (five years if you also receive Medicaid). If you subscribe to a higher level of service and receive (INSERT NAME OF CABLE BASIC SERVICE TIER OFFERING) on a secondary TV without (NAME OF CABLE OPERATOR)-supplied equipment, you are entitled to one device for one year.

You can learn more about this equipment offer and eligibility at (WEBPAGE ADDRESS) or by calling (PHONE NUMBER). To qualify for any equipment at no additional charge or service fee, you must request the equipment between (DATE THAT IS 30 DAYS BEFORE ENCRYPTION) and (DATE THAT IS 120 DAYS AFTER ENCRYPTION) and satisfy all other eligibility requirements.

(vi) The cable system operator notifies its subscribers who have received equipment described in paragraphs (a)(1)(ii) through (iv) of this section at